


# 4DLCD-35480320-IPS Series

4DLCD-35480320-IPS  
4DLCD-35480320-IPS-RTP  
4DLCD-35480320-IPS-CTP  
4DLCD-35480320-IPS-CTP-CLB



## Datasheet

Revision 1.3

Copyright © 2024 4D Systems

Content may change at any time. Please refer to the resource centre for latest documentation.

# Contents

---

1. General Specification	4
2. TFT LCD Display Drawing (Non-Touch Version)	0
3. TFT LCD Display Drawing (Resistive Touch Version)	0
4. TFT LCD Display Drawing (Capacitive Touch Version)	0
5. TFT LCD Display Drawing (Capacitive Touch Version with Cover Lens Bezel)	0
6. Absolute Maximum Ratings	0
7. Electrical Characteristics	0
8. Electro-Optical Characteristics	0
9. Backlight Characteristics	0
10. Interface Descriptions	0
10.1. LCD Interface	0
10.2. CTP Interface	0
11. Backlight Example Circuit	0
12. Initialisation Code	0
13. LCD Timing Details	0
13.1. Timing Chart	0
13.2. Reset Timing	0
13.3. Power On Sequence	0
13.3.1. Case 1 - RES line is held High or Unstable by Host at Power ON	0
13.3.2. Case 2 - RES line is held Low by Host at Power ON	0
13.4. Power-off Sequence - Uncontrolled Power Off	0
14. Reliability Test	0
15. Precautions for Using LCD Modules	0
15.1. Handling Precautions	0
15.2. Storage Precautions	0
16. Revision History	0
17. Legal Information	0
17.1. Proprietary Information	0



## 1. General Specification

4DLCD-35480320-IPS is a colour active-matrix LCD module incorporating amorphous silicon IPS TFT (Thin Film Transistor). It is composed of a colour TFT-LCD panel, driver IC, FPC and a backlight unit with/without a Resistive/ Capacitive Touch Panel (RTP or CTP), and with/without Cover Lens Bezel (CLB). The module display area contains 320 x 480 pixels. This product accords with RoHS environmental criteria.

### Part Number Details:

4DLCD - 4D Systems LCD Display

3548032 - 3.5-inch, 320 x 480 Resolution

RTP - Resistive Touch

CTP - Capacitive Touch

CLB - Cover Lens Bezel



### Note

- RoHS compliant
- LCD weight tolerance:  $\pm 5\%$ .